

Compare Products

Code	70971
Model	XK



Note

✘
 - Top speed is delivered with fully charged battery
 - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim
 - Conditions : sea water - no flow/current

Dimensions

Use	TECH / COMMERCIAL LONG RANGE / CAVE
Length	mm 975 (inch 38,4)
Width	mm 462 (inch 18,2)
Height	mm 364 (inch 14,33)
Body diameter	mm 197 (inch 7,8)
Weight without battery	kg 17 (lb 37,48)
Weight with battery	kg 25 (lb 55,12)
Material type	Body in Nautical Aluminum

Performance

Max static thrust	N 370 (lb 83,2)
Top speed	mt/min 100 (ft/min 328)
Run time at max speed/drag	min 100
Run time at cruise speed	min 330
Maximum operational depth	mt 200 (ft 656)
Test depth	mt 300 (ft 984)

Buoyancy/ trim	Neutral Trim and Buoyancy															
In-water usage temperature	°C -5/+35 (°F +23/+95)															
Runtime-range	<table border="1"> <thead> <tr> <th>SPEED MT/MIN</th> <th>BURNTIME - MIN</th> <th>RANGE KM (nm)</th> </tr> </thead> <tbody> <tr> <td>FULL TRIGGER</td> <td>100</td> <td>8,1 (4,3)</td> </tr> <tr> <td>80</td> <td>120</td> <td>9,6 (4,9)</td> </tr> <tr> <td>60- 2 KNOTS</td> <td>200</td> <td>12,0(7,0)</td> </tr> <tr> <td>45 - CRUISE</td> <td>330</td> <td>14,8(7,5)</td> </tr> </tbody> </table>	SPEED MT/MIN	BURNTIME - MIN	RANGE KM (nm)	FULL TRIGGER	100	8,1 (4,3)	80	120	9,6 (4,9)	60- 2 KNOTS	200	12,0(7,0)	45 - CRUISE	330	14,8(7,5)
	SPEED MT/MIN	BURNTIME - MIN	RANGE KM (nm)													
	FULL TRIGGER	100	8,1 (4,3)													
	80	120	9,6 (4,9)													
	60- 2 KNOTS	200	12,0(7,0)													
45 - CRUISE	330	14,8(7,5)														
- Top speed is delivered with fully charged battery																
- Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim																
- Conditions : sea water - no flow/current																

Battery type

Battery type	LI-ion
Nominal Voltage	Volt 36
Nominal Capacity	Wh 1340
Maximum recharging time	h 8
Charger power supply	90/240 - 50/60 Hz

Features

DRIVE	●
Fastening device	●
Main Switch	●
Proplock Propeller	●
Speed Adjustment	●
Battery Gauge	●
By-pass System	●
Easy Trim	●
Easy Inspect	●
New Handle Design	●
Battery and Charger Design and Quality	●
Sealed Motor Compartment	●
NBS - Neutral Buoyancy System	●
Made Salt Resistant	●
Motor Protection	●
Battery Protection	●
Certifications	●

Features legend:

- : standard
- : optional
- : not available